

ENRICHING YOUR DIGITAL EXPERIENCE

NEW MEMBER TO WORLD'S MOST COMPLETE DMR PORTFOLIO

PD982



PD98X Highlight Brand New Features

01

Micro SD Card

PD982 uses micro DS storage technology to allow recording and storage of critical voice calls or data transmissions.


PD98X supports maximum 32G micro SD card, to record up to 576 hours digital/ analog voice.



02

Single Frequency Repeater Mode

Using interference cancellation technique, PD982 can use one slot to receive signal and another slot to transmit it on the same frequency at the same time, extending communications distance in DMO mode.



03

Bluetooth 4.0

PD982 has built in Bluetooth 4.0, which not only supports audio transmission, but also allows data transmission, such as programming via Bluetooth etc.

04

Full Duplex Call

PD982 can make full duplex calls with other PD982, telephones or cellphones.

05

RTC Clock

RTC clock feature allows customers to check the accurate time of received message and call.

06

Smart Battery

Compared with PD78X, PD98X support smart battery, which makes it easier to monitor the battery status, such as battery life time and remaining charge time by smart battery charge. This also reduces the charging time dramatically.

360 Degree Seamless Channel Knob Turn



Centered Antenna

Integrated GPS and RF antenna, more accurate positioning and receiving.




1.8 Inch High Definition Display

Displaying clear contents.

IP68 Protection



Better Sensitivity and Frequency Stability



Enhanced Voice Quality




Longer Battery Life



Bluetooth 4.0



Micro SD Card



Single Frequency Repeater Mode



Full Duplex Call



RTC Clock



Smart Battery

PD982 Highlight Hardware Advantages



Better Sensitivity and Frequency Stability

Advanced technology improves receiving performance to enhance communication distance and reliability.



Sensitivity 26%+

Compared with PD782, PD982 adopts brand new hardware design enhanced with 26% more sensitivity.



Longer Battery Life

PD982 adopts new battery saving technology to guarantee longer communication time.



Battery life 33%+

Compared with PD782, PD982 adopts new battery saving technology providing 33% more battery life.



IP68 Protection

IP68 Dust and Waterproof Standards ensures outstanding performance even in harsh environments.



360°Seamless Channel Knob Turn With

With this kind of knob, users can change channels and zone easily and comfortably.



Enhanced Voice Quality

Maximum 2.5W output speaker and new noise cancelling technology ensures clear and loud voice communication.

Noisy environment

Figure 1 Without noise cancellation



Figure 2 With noise cancellation



Windy environment

Figure 1 Without echo cancellation



Figure 2 With echo cancellation



Features

Base Information

- Full Keypad, Color Screen, 1024 Channels
- Analog and Digital Dual Mode
- Bluetooth (4.0) Audio
- Bluetooth (4.0) Data*
- Integrated GPS
- Integrated GLONASS
- Pre-programmed Text Messaging
- Freeform Text Messaging
- Option Board
- Roaming
- Scan
- Voice Notification

Audio

- Auto Gain Control
- Acoustic Feedback Suppressor
- Loudness Quality Optimization
- Multi Band Equalization*
- Noise Reduction Technology

NOTES

- * These features will be available later by software upgrade upgrade
- Standard feature
- Optional feature

Safety

- Emergency Alarm
- Dedicate Emergency Button
- Alert Call
- Man Down
- Lone Worker
- Basic Encryption
- Enhanced Encryption(40bit)
- Enhanced Encryption(128/256bit)
- Multiple Key Encryption
- Priority Interrupt
- Remote Monitor
- Radio Enable/Disable
- Radio Check
- IP68 Dust and Waterproof
- Vibration
- GPS SMS
- GPS Location check

Systems

- Analog Conventional
- DMR Conventional
- IP Site Connect
- MPT-1327
- DMR Simulcast System
- XPT Trunking
- DMR Trunking

Advance Features

- Pseudo Trunk
- Telemetry
- Rent
- Phone Interconnect
- Full Duplex Call (DMR Tier 3 System)*
- Full Duplex Call (DMR Conventional System)*
- Single Frequency Repeater Mode*
- Micro SD Card*
- Smart Battery*
- RTC Clock
















Specifications

General	Frequency Range	UHF: 350-527MHz		
	Channel Capacity	1024		
	Zone Capacity	64 (maximum of 128 channels per zone)		
	Channel Spacing	12.5KHz / 20KHz / 25KHz		
	Operating Voltage	7.4V (rated)		
	Battery	2000mAh (Li-Ion)		
	Battery Life (5-5-90 Duty Cycle, High TX Power) High-capacity 2000mAh Li-Ion Battery	Analog:14.5h	Digital: 19.5h	
	Frequency Stability	• 0.5ppm		
	Antenna Impedance	50• •		
	Dimensions (H• W• D) (with standard battery, without antenna)	131 X 54.5 X 36mm		
	Weight (with antenna & standard battery)	12oz.		
	LCD Display	160• 428 pixels, 65535 colors 1.8 inch, 4 rows		
	Receiver	Sensitivity	Analog	0.22µV
Digital			0.22• ▼/BER5%	
Selectivity TIA-603 ETSI C		60dB @ 12.5KHz / 70dB @ 20/25KHz 60dB @ 12.5KHz / 70dB @ 20/25KHz		
Spurious Response Rejection TIA-603 ETSI C		70dB @ 12.5/20/25KHz 70dB @ 12.5/20/25KHz		
Blocking TIA-603 ETSI		84dB		
Hum and Noise		40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz		
Rated Audio Power Output		0.5W		
Rated Audio Distortion		• 8%		
Audio Response		+1 ~ -3dB		
Conducted Spurious Emission		< -57dBm		

Transmitter	RF Power Output	UHF High Power: 4W• UHF Low Power: 1W	
	FM Modulation	11K0F3E @ 12.5KHz 14K0F3E @ 20KHz 16K0F3E @ 25KHz	
	4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW	
	Modulation Limiting	±2.5KHz @ 12.5KHz ±4.0KHz @ 20KHz; ±5.0KHz @ 25KHz	
	FM Hum & Noise	40dB @ 12.5KHz 43dB @ 20KHz 45dB @ 25KHz	
	Adjacent Channel Power	60dB @ 12.5KHz; 70dB @ 20/25KHz	
	Audio Response	+1 ~ -3dB	
	Audio Distortion	• 8%	
	Digital Vocoder Type	AMBE++or SELPor NVOC	
	Digital Protocol	ETSI-TS102 361-1,-2,-3	
Environmental Specifications	Operating Temperature	-30• ~ +60• •	
	Storage Temperature	-40• ~ +85• •	
	ESD	IEC 61000-4-2 (level 4) ±8kV (contact) ±15kV (air)	
	American Military Standard	MIL-STD-810 C/D/E/F/G	
	Dust & Water Intrusion	IP68 Standard	
	Humidity	Per MIL-STD-810 C/D/E/F/G Standard	
	Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard	

GPS	Accuracy specs are for long-term tracking(95th percentile values>5 satellites visible at a nominal -130dBm signal strength)		
	TTFF (Time To First Fix) Cold Start	<1 minute	
	TTFF (Time To First Fix) Hot Start	<10 seconds	
	Horizontal Accuracy	<10 meters	

Optional Accessories

							
Remote Speaker Microphone (IP57) SM18N2	C-Earset EHN16	Swivel Earset EHN17	Earbud ESN12	3-Wire Surveillance Earpiece with Transparent Acoustic Tube (beige) EAN17	Receive-only Earpiece ESS08	Six-Unit Switching Power Supply PS7002	Programming Cable (USB Port) PC38
					Pictures above are for reference only and may vary from actual products. Contact your dealer for more accessories information.		
Battery Optimizing System MCA05	MCU Multi-unit Charger (for Thick Battery) MCA08	3-wire Surveillance Earpiece with Transparent Acoustic Tube(Black) EAN18	2-wire Earpiece with Wireless Earphone and Neck Loop(Beige) EWN06	Receive-only Earpiece ESS07			

Terry D. Gillard - NX7R

TTG Communications Co.
1004 San Gabriel Ave
Henderson, Nevada 89002

web: www.ttgcommunications.com
 email: hytera.nv@gmail.com
 fb: <https://www.facebook.com/ttgcommunications>



Hytera America

Address: 3315 Commerce Parkway
 Miramar, Florida 33025, USA
Tel: 800-845-1230 **Fax:** 954-846-1672
<http://www.hytera.us>

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.
 ©2016 Hytera Communications Corp., Ltd. All Rights Reserved.